# PROPAGATION AND SCATTERING IN LAYERS WITH ROUGH INTERFACES: SHALLOW WATER ACOUSTICS

David H. Berman
Department of Physics and Astronomy
University of Iowa
Iowa City, IA 52242
phone: 319-335-1223
FAX: 319-335-1753

e-mail: Berman@iowa.physics.uiowa.edu Award #: N00014-95-0754 MOD 2

#### LONG-TERM GOAL

This research is being pursued in order provide good approximations for the behavior of acoustic fields propagating in layers bounded by statistically rough interfaces and to understand the importance of multiple scattering between interfaces.

## SCIENTIFIC OBJECTIVE

The immediate scientific objective of this research is to develop improved methods for computing the mean and the second moments of acoustic fields in waveguides with rough boundaries. Of particular concern is the problem of surface scattered fields returning to interact with a scattering interface many times. A secondary objective is to determine how to incorporate non-perturbative scattering amplitudes which have been developed for half-space scattering into the description of scattering in a waveguide where plane-waves do not provide a natural description of propagation.

#### **APPROACH**

In a waveguide with many interfaces, the net field incident on one particular interface is the result of adding the field arising directly from any sources and the field which is multiply reflected

and scattered from the remainder of the waveguide. The scattered field is determined by this net incident field plus the result of this field after it has been multiply scattered. To describe this complicated situation I have developed a compact formulation of the scattering in a waveguide with arbitrary sound speed profile which uses impedance operators to describe the effects of rough interfaces. This formulation is analogous to multiple scattering formalisms used in solid state physics to describe electron localization, and I have been able to adapt the methods used there to multimodal propagation in waveguides.

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding an DMB control number.	ion of information. Send comments arters Services, Directorate for Info	s regarding this burden estimate ormation Operations and Reports	or any other aspect of the s, 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 30 SEP 1997	2 DEPORT TYPE			3. DATES COVERED <b>00-00-1997 to 00-00-1997</b>		
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Propagation and Scattering in Layers with Rough Interfaces: Shallow Water Acoustics				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  University of Iowa, Department of Physics and Astronomy, Iowa City, IA, 52242				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAIL Approved for publ	ABILITY STATEMENT ic release; distributi	on unlimited				
13. SUPPLEMENTARY NO	OTES					
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>	Same as Report (SAR)	3		

**Report Documentation Page** 

Form Approved OMB No. 0704-0188

# WORK COMPLETED AND RESULTS

The formalism mentioned above has been developed in detail to give the a formula for the scattered field in which the scattered field is given by the mean propagator from the sources to the interfaces followed by a multiple scattering operator, followed again by the mean propagator from the interfaces to the receiver. In this formula it is actually the vertical derivative of the mean propagators that appears rather than the mean propagator itself. The form of the fluctuating Green function is explicitly reciprocal. The appearance of derivatives of the mean field at the surfaces is, I believe, a new result.

I have used this formalism to see what effects multiple scattering might have on reverberation time histories. Because the mean field is used to propagate to and from the surfaces there is some extra attenuation that would be missed in a more conventional treatment. More importantly, the effective scattering operator in the ladder approximation (i.e. the scattering operator computed as an infinite sum of simple scattering) exhibits diffusive behavior. The importance of this for reverberation is that in addition to modal contributions that decay in time exponentially, there is a diffusive contribution that decays only as 1/t. The exponential behavior has been described by Ellis, starting from a much more phenomenological approach. He does not mention diffusive contributions.

The electron localization work is concerned with a class of multiple scattering events which gives rise to even slower decay --in fact, to no decay. As I understand things now, this would imply a sort of fossil'sound in the reverberation context. However, that supposes that there is no intrinsic attenuation--that the mean field is attenuated only because of energy-conserving scattering. The effect of these multiple scattering events has been observed in enhanced backscattering. It would be interesting if there were also a noticeable temporal effect.

## IMPACT/APPLICATION

The most important impact of this work is the questions it raises:

- 1) Are the echoes predicted by this computation observable? Are there long echoes in other settings, particularly settings in which a signal impinges from the outside on a rough layer?
- 2) Will the presence of diffusive behavior alter the interpretation of acoustic measurements of
- sea-floor topography?
- 3) Does the diffusive pole affect forward scattering? How might it affect the coherence of and signal processing of forward scattered signals?

# **RELATED PROJECTS**

A number of authors have treated the problem of propagation in waveguides with rough boundaries, for example, Beran and Frankenthal. For the most part, these treatments rely on parabolic or in some other sense one-way treatments of the scattering. The method used here makes no use of parabolic approximations, which is why one can discuss reverberation.

# **REFERENCES**

Dale D. Ellis, J. Acoust. Soc. Am. 97, 2804 (1995).M. J. Beran and S. Frankenthal, J. Acoust. Soc. Am. 91 3203 (1992).